

Safety at the press of a button

INTERex 25/50

Chemical-free ambient air disinfection with UV-C



INTERex®

INTERex 25/50 UV-C Disinfection Solutions

Say goodbye to viruses, bacteria and fungi. UV-C light makes germs in the ambient air harmless. Simply press the start button and experience how good it feels to be safe.

Infectioncontrol



INTERex 25/50 disinfects the ambient air with UV-C with total reliability. Its effectiveness has been clinically tested and proven.

Protect your future

INTERex 25/50 is effective against new germs too and safeguards your company.

Just as you choose


INTERex 25/50 is flexible and meets individual requirements. You get exactly what you need.

Functional description



UV-C light is short-wave and loaded with energy.

Used selectively, it destroys the DNA - i.e. the genetic information - of viruses, bacteria and other germs. This prevents the reproduction of pathogens and thus renders them harmless. Did you know? The sun also emits UV-C light. Because of the ozone layer, however, it does not reach the earth's surface.



Features



Environmentally friendly disinfection. Free of chemicals and ozone.



No external UV-C radiation. No toxic interchangeable filters.



Digitally validated and certified.

Award winning



Best Product and Best Brand 2021

The GoGaS INTERx series for chemical-free ambient air disinfection wins the internationally renowned PLUS-X Award 2021 as Best Product and Best Brand 2021 in the category room disinfection. This means we offer a unique, complete range of precisely fitting systems for infection control in all areas of any building. Safety without compromises.

Technical data

Installation	Wall- or ceiling-mounted
External dimensions	Lenght: 800 mm; Width: 400 mm; Height: 140 mm
Total weight	7 kg
Enclosure material	Stainless Steel, Aluminium
Color	Silver
Ambient temperature, operation	5 to 45 °C
Electrical connection	230 V AC voltage, 50 Hz
Electrical connection power rating	45W/ 75W
UV-C-wavelength	254 nm (disinfecting, min. log level 3; 99.9%)
Max. air flow	$25 \text{ m}^3/\text{h}$ (noise level $\leq 35 \text{dBA}$)
Radiant power	> 220 Joule/m ²
Illuminant	Service life > 9.000 h
Pre-filter	Filtration class G3 (dust/dirt)
Safety	Fully automatic operation with fail-safe function.
Made in Germany; CE; EMC Directive 2014/30/EU; Low Voltage Directive 2014/35/EU; RoHS 2 Directive 2011/65/EU; Photobiological Safety EN 62471; Protection class IP20.	

Certified:

Partnership:





We'll always be glad to help you!

